

TURBO 634




60 to 120
m²

SUPRO.

WITH ITS TRADITIONAL APPEARANCE, THIS INSERT IS PERFECT FOR A RUSTIC AND WARM INTERIOR.

INSERTS



COMBUSTION AND MATERIALS

- 2 turbines en standard to distribute the heat in the room
- High-performance cast iron heating element
- Cast-iron grating and sill
- Heavy-duty glass ceramic door

INSTALLATION AND USE

- Single air control to regulate combustion
- Easy access and large capacity ashtray for spaced ash removal
- Front opening door
- "Clean glass" system

- Can be installed without a flue duct in an open fireplace.

The hot flue gases pass between the heat exchanger tubes and are sent directly into the exhaust duct of the old fireplace; during installation there is no connection work to be carried out on the old flue duct.

PRODUCT PERFORMANCE

Nominal power	6 kW
Power range	3 to 10 kW
Efficiency	78 %
Seasonal efficiency	68 %
CO (13 % O ₂) (%/mg/Nm ³)	0.103 - 1282
Nominal load	1.8 kg/h
Dust (mg/Nm ³)	29
NO _x (mg/Nm ³)	117
COV (OGC) (mg/Nm ³)	89
Mean flue gas temperature	242 °C
Flue gas mass flow	7.5 g/s
Nozzle depression (nominal)	12 Pa
CO ₂ emissions	7.16 %
Dual combustion	No
Airlight	No
ECODESIGN 2022	Yes

PRODUCT INFORMATION

EAN Code:	311 983 112 021 8
Product code	FR9005550B
Main material	Steel
View of the fire (diagonal)	58 cm (26 inch)
Log size	45 cm (50 cm MAX.)
Gross weight	97 kg
Net Weight	78 kg
Dimensions LxHxD	63 x 53 x 41.5 cm
Packaging dimensions LxHxD	60 x 76 x 80 cm

INSTALLATION AND SIZING

Diameter of flue gas nozzle	-
Flue gas connection	-
Flue collar	-
Diameter connection to outside air	-
Back installation distance*	0 cm
Lateral installation distance*	0 cm

*Distance between the heater and combustible materials

See options available at the end of the catalogue

PRODUCT PHOTOS



Rustic style hearth plate interior to add character to your fireplace.



The manual ventilation is switched on by means of a switch on the front of the appliance.

DIMENSIONAL PLAN

