

# NÉO 67



80 to 160  
m<sup>2</sup>

SUPRO.

MODERN AND CHIC, THE NEO RANGE ENHANCES THE ELEGANCE OF YOUR HOME.

INSERTS



## COMBUSTION AND MATERIALS

- **Dual combustion** for more efficient and cleaner combustion (minimum CO and dust content)
- **RE 2020 COMPATIBLE SEAL:** high level of airtightness allows combustion air control (fully channelled and controllable primary air, secondary air and window air)
- **Cast iron hearth plate** for extra strength
- Cast-iron grating and sill
- Screen-printed glass door
- **Standard frame for a perfect finish**
- High-strength ceramic glass

## INSTALLATION AND USE

- **Ingenious design suitable for both the installation of open fireplaces and the creation of fireplaces.**
- Top flue connection (150 mm)
- Standard protective coating
- Possibility of hot air distribution
- Turbine: 2 ventilation powers (180m<sup>3</sup>/h)-(optional)
- Single air control to regulate combustion
- **"Clean glass" system**
- Large view of the fire diagonal 56 cm (24 inches)
- Removable large capacity ashtray

PRODUCT PERFORMANCE	
Nominal power	8 kW
Power range	5 to 14 kW
Efficiency	85 %
Seasonal efficiency	75 %
CO (13 % O <sub>2</sub> ) (%/mg/Nm <sup>3</sup> )	0.09 - 1170
Nominal load	2.25 kg/h
Dust (mg/Nm <sup>3</sup> )	4
NO <sub>x</sub> (mg/Nm <sup>3</sup> )	110
COV (OGC) (mg/Nm <sup>3</sup> )	120
Mean flue gas temperature	174 °C
Flue gas mass flow	6.8 g/s
Nozzle depression (nominal)	12 Pa
CO <sub>2</sub> emissions	9.1 %
Dual combustion	Yes
Airlight	Yes
ECODESIGN 2022	Yes

PRODUCT INFORMATION	
EAN Code:	311 983 <b>112 039 3</b>
Product code	FR9006720B
Main material	Steel
View of the fire (diagonal)	56 cm (22 inch)
Log size	50 cm (55 cm MAX.)
Gross weight	110 kg
Net Weight	99 kg
Dimensions LxHxD	70.8 x 59.5 x 48.3 cm
Packaging dimensions LxHxD	76 x 76 x 57 cm

INSTALLATION AND SIZING	
Diameter of flue gas nozzle	150 mm
Flue gas connection	Top
Flue collar	Male
Diameter connection to outside air	75 mm (back or down)
Back installation distance*	5 cm
Lateral installation distance*	5 cm

\*Distance between the heater and combustible materials

See options available at the end of the catalogue

## PRODUCT PHOTOS



Lever handle (NEO 67, 76, 76 16:9, 100 and 55).



Interior of hearth plate, hearth plate and cast iron grates (NEO 55, 67, 76 and 76 16/9ÈME).

## DIMENSIONAL PLAN

