

GREAT VIEW OF THE FIRE, GREAT RESISTANCE AND GREAT WOODSHED.

HORIZONTAL CAST IRON STOVES



COMBUSTION AND MATERIALS

- **Dual combustion** for more efficient and cleaner combustion (minimum CO and dust content)
- **RE 2020 COMPATIBLE SEAL:** high level of airtightness allows combustion air control (fully channelled and controllable primary air, secondary air and window air)
- **High density vermiculite interior** for increased resistance to extremetemperatures and improved combustion
- Removable cast iron grating
- High-strength ceramic glass

INSTALLATION AND USE

- **Back or top flue connection** (150 mm)
- Back protection to reduce the rear side temperature
- Small installation distance can be positioned 25 cm from the wall
- Load facilitated by its high height
- Adjustable primary and secondary air
- "Clean glass" system
- Large view of the fire diagonal 64 cm (25 inches)
- Removable large capacity ashtray

PRODUCT PERFORMANCE	
Nominal power	8.5 kW
Power range	6 to 12 kW
Efficiency	75.4 %
Seasonal efficiency	65.4 %
CO (13 % O ₂) (mg/Nm ³)	0.09 - 1080
Nominal load	2 kg/h
Dust (mg/Nm ³)	20
NOx (mg/Nm ³)	97
COV (OGC) (mg/Nm ³)	73
Mean flue gas temperature	313 °C
Flue gas mass flow	8.3 g/s
Nozzle depression (nominal)	12 Pa
CO ₂ emissions	9.38 %
Dual combustion	Yes
Airlight	Yes
ECODESIGN 2022	Yes

PRODUCT INFORMATION	
EAN Code:	376 007 541149 7
Product code	FR9010560B
Main material	Steel
View of the fire (diagonal)	64 cm (25 inch)
Log size	50 cm (62 cm MAX.)
Gross weight	131 kg
Net Weight	109 kg
Dimensions LxHxD	76.3 x 70.1 x 39.2 cm
Packaging dimensions LxHxD	83 x 88 x 53 cm

INSTALLATION AND SIZING	
Diameter of flue gas nozzle	150 mm
Flue gas connection	Back or above part
Flue collar	Male
Diameter connection to outside air	100 mm (back)
Back installation distance*	25 cm
Lateral installation distance*	20 cm

*Distance between the heater and combustible materials

PRODUCT PHOTOS



Integrated woodshed length of 76 cm for storing firewood within easy.



Ergonomic handle adapted for its everyday use.

DIMENSIONAL PLAN

