


NEW

PAUL



SUPRA.

THE PAUL RANGE IS SUITABLE FOR BOTH MODERN AND TRADITIONAL INTERIORS.

HORIZONTAL CAST IRON STOVES



COMBUSTION AND MATERIALS

- Dual combustion for more efficient and cleaner combustion (minimum CO and dust content)
- Vermiculite baffle
- Made of high quality lamellar graphite cast iron
- Double wall cast iron for extra strength
- Removable cast iron grating
- High-strength ceramic glass

INSTALLATION AND USE

- Back or **top flue connection** (150 mm)
- Back protection to reduce the rear side temperature
- Small installation distance can be positioned 30 cm from the wall
- Adjustable primary and secondary air
- "Clean glass" system to avoid frequent maintenance
- Large capacity removable ashtray

PRODUCT PERFORMANCE	
Nominal power	10 kW
Power range	6 to 14 kW
Efficiency	77 %
Seasonal efficiency	67 %
CO (13 % O ₂) (mg/Nm ³)	0,10 / -
Nominal load	2.9 kg/h
Dust (mg/Nm ³)	18
NO _x (mg/Nm ³)	105
COV (OGC) (mg/Nm ³)	99
Mean flue gas temperature	314 °C
Flue gas mass flow	-
Nozzle depression (nominal)	12 Pa
CO ₂ emissions	10.4 %
Dual combustion	Yes
Airlight	No
ECODESIGN 2022	Yes

PRODUCT INFORMATION	
EAN Code:	376 007 541 318 7
Product code	FR9015970B
Main material	Cast iron
View of the fire (diagonal)	52.5 cm (21 inch)
Log size	50 cm
Gross weight	175 kg
Net Weight	160 kg
Dimensions LxHxD	70.2 x 73.2 x 43.2 cm
Packaging dimensions LxHxD	72 x 85.7 x 48 cm

INSTALLATION AND SIZING	
Diameter of flue gas nozzle	150 mm
Flue gas connection	Back or above part
Flue collar	Male
Back installation distance*	30 cm
Lateral installation distance*	45 cm

*Distance between the heater and combustible materials

PRODUCT PHOTOS



Integrated handle for an elegant design (PAUL, PAUL HAUT, PAUL BÜCHER AND PAUL SUR PIED).



Curved view of the fire , diagonal 52.5 cm (21 inches)(PAUL, PAUL HAUT, PAUL BÜCHER AND PAUL SUR PIED).

DIMENSIONAL PLAN

