

NEW

PAUL BÛCHER




100 to 200
m²

SUPRA.

THE WOOD BURNER THAT HAS IT ALL! ORIGINAL VIEW OF THE FIRE THANKS TO ITS CURVED GLASS AND ITS INTEGRATED WOODSHED.

HORIZONTAL CAST IRON STOVES



COMBUSTION AND MATERIALS

- Dual combustion for more efficient and cleaner combustion (minimum CO and dust content)
- Vermiculite baffle
- Made of high quality lamellar graphite cast iron
- Double wall cast iron for extra strength
- Removable cast iron grating
- High-strength ceramic glass

INSTALLATION AND USE

- Back or top flue connection (150 mm)
- Back protection to reduce the rear side temperature
- Small installation distance can be positioned 30 cm from the wall
- Load facilitated by its high height
- Adjustable primary and secondary air
- "Clean glass" system to avoid frequent maintenance
- **Curved diagonal view of 52.5 cm (21 inches)**
- Large capacity removable ashtray

PRODUCT PERFORMANCE

Nominal power	10 kW
Power range	6 to 14 kW
Efficiency	77 %
Seasonal efficiency	67 %
CO (13 % O ₂) (mg/Nm ³)	0,10 / -
Nominal load	2.9 kg/h
Dust (mg/Nm ³)	18
NO _x (mg/Nm ³)	105
COV (OGC) (mg/Nm ³)	99
Mean flue gas temperature	314 °C
Flue gas mass flow	-
Nozzle depression (nominal)	12 Pa
CO ₂ emissions	10.4 %
Dual combustion	Yes
Airlight	No
ECODESIGN 2022	Yes

PRODUCT INFORMATION

EAN Code:	376 007 541 319 4
Product code	FR9015980B
Main material	Cast iron
View of the fire (diagonal)	52.5 cm (21 inch)
Log size	50 cm
Gross weight	190 kg
Net Weight	175 kg
Dimensions LxHxD	70.2 x 87.7 x 43.2 cm
Packaging dimensions LxHxD	72 x 100 x 48 cm

INSTALLATION AND SIZING

Diameter of flue gas nozzle	150 mm
Flue gas connection	Back or above part
Flue collar	Male
Back installation distance*	30 cm
Lateral installation distance*	45 cm

*Distance between the heater and combustible materials

PRODUCT PHOTOS



Integrated handle for a elegant design (PAUL, PAUL HAUT, PAUL BÛCHER AND PAUL SUR PIED).



Integrated woodshed length of 70 cm for storing firewood within easy

DIMENSIONAL PLAN

