


NEW


PAUL SUR PIED



SUPRO.

SILHOUETTE OF A WOOD BURNER WITH FEET: ATTRACTIVE ROUNDED SHAPES

HORIZONTAL CAST IRON STOVES



COMBUSTION AND MATERIALS

- Dual combustion for more efficient and cleaner combustion (minimum CO and dust content)
- Vermiculite baffle
- Made of high quality lamellar graphite cast iron
- Double wall cast iron for extra strength
- Removable cast iron grating
- High-strength ceramic glass

INSTALLATION AND USE

- Back or top flue connection (150 mm)
- Rear protection to protect any nearby installations
- Small installation distance can be positioned 30 cm from the wall
- Load facilitated by its high height
- Adjustable primary and secondary air
- "Clean glass" system to avoid frequent maintenance
- Removable large capacity ashtray

PRODUCT PERFORMANCE

Nominal power	10 kW
Power range	6 to 14 kW
Efficiency	78 %
Seasonal efficiency	68 %
CO (13 % O ₂) (mg/Nm ³)	0,10 / -
Nominal load	2.9 kg/h
Dust (mg/Nm ³)	18
NO _x (mg/Nm ³)	105
COV (OGC) (mg/Nm ³)	99
Mean flue gas temperature	314 °C
Flue gas mass flow	-
Nozzle depression (nominal)	12 Pa
CO ₂ emissions	10.4 %
Dual combustion	Yes
Airlight	No
ECODESIGN 2022	Yes

PRODUCT INFORMATION

EAN Code:	376 007 541 320 0
Product code	FR9015990B
Main material	Cast iron
View of the fire (diagonal)	52.5 cm (21 inch)
Log size	50 cm
Gross weight	200 kg
Net Weight	185 kg
Dimensions LxHxD	70.2 x 83.2 x 43.2 cm
Packaging dimensions LxHxD	72 x 95.7 x 48 cm

INSTALLATION AND SIZING

Diameter of flue gas nozzle	150 mm
Flue gas connection	Back or above part
Flue collar	Male
Back installation distance*	30 cm
Lateral installation distance*	45 cm

*Distance between the heater and combustible materials

PRODUCT PHOTOS



Integrated handle for an elegant design (PAUL, PAUL HAUT, PAUL BÜCHER AND PAUL SUR PIED).



Curved view of the fire , diagonal 52.5 cm (21 inches) (PAUL, PAUL HAUT, PAUL BÜCHER AND PAUL SUR PIED).

DIMENSIONAL PLAN

