


NEW

LARRY SUR PIED



SUPRO.

CREATING A DISTINGUISHED AND UNIQUE ENVIRONMENT

HORIZONTAL CAST IRON STOVES



| | | | | |
|--|------------------------|---------------------------|-----------------------------|--|
| | POWER 8.5 kW | 50 cm (62 cm MAX.) | AIRTIGHT AND CONNECTIBLE | CONNECTED TO OUTSIDE AIR (in diameter) 100 mm |
|--|------------------------|---------------------------|-----------------------------|--|

COMBUSTION AND MATERIALS

- **Dual combustion** for more efficient and cleaner combustion (minimum CO and dust content)
- **RE 2020 COMPATIBLE SEAL:** high level of airtightness allows combustion air control (fully channelled and controllable primary air, secondary air and window air)
- **High density vermiculite interior** for increased resistance to extremetemperatures and improved combustion
- Removable cast iron grating
- High-strength ceramic glass

INSTALLATION AND USE

- **XL size:** this heater will set you on fire with its energy and environmental performances.
- Back or top flue connection (150 mm)
- **Back protection** to reduce the rear side temperature
- Small installation distance can be positioned **25 cm from the wall**
- Load facilitated by its high height
- Adjustable primary and secondary air
- **"Clean glass" system**
- Removable large capacity ashtray

PRODUCT PERFORMANCE

| | |
|---|-------------|
| Nominal power | 8.5 kW |
| Power range | 6 to 12 kW |
| Efficiency | 75.4 % |
| Seasonal efficiency | 65.4 % |
| CO (13 % O ₂) (%/mg/Nm ³) | 0.09 - 1080 |
| Nominal load | 2 kg/h |
| Dust (mg/Nm ³) | 20 |
| NO _x (mg/Nm ³) | 97 |
| COV (OGC) (mg/Nm ³) | 73 |
| Mean flue gas temperature | 313 °C |
| Flue gas mass flow | 8.3 g/s |
| Nozzle depression (nominal) | 12 Pa |
| CO ₂ emissions | 9.38 % |
| Dual combustion | Yes |
| Airlight | Yes |
| ECODESIGN 2022 | Yes |

PRODUCT INFORMATION

| | |
|-----------------------------|--------------------------|
| EAN Code: | 376 007 541 322 4 |
| Product code | FR9016010B |
| Main material | Steel |
| View of the fire (diagonal) | 64 cm (25 inch) |
| Log size | 50 cm (62 cm MAX.) |
| Gross weight | 155 kg |
| Net Weight | 145 kg |
| Dimensions LxHxD | 76.3 x 69.9 x 39.1 cm |
| Packaging dimensions LxHxD | 83 x 88 x 53 cm |

INSTALLATION AND SIZING

| | |
|------------------------------------|--------------------|
| Diameter of flue gas nozzle | 150 mm |
| Flue gas connection | Back or above part |
| Flue collar | Male |
| Diameter connection to outside air | 100 mm (back) |
| Back installation distance* | 25 cm |
| Lateral installation distance* | 20 cm |

*Distance between the heater and combustibile materials

PRODUCT PHOTOS



This heater turns up the heat!
Its straight-lined design creates a distinguished ambience.



Ergonomic handle adapted for its everyday use.

DIMENSIONAL PLAN

