

NEW


# MAONIE SUR PIED



SUPRA.

A GREAT VERTICAL VIEW OF THE FLAME WITH A SINGLE FOOT

VERTICAL STEEL WOOD STOVES



## COMBUSTION AND MATERIALS

- **Dual combustion** for more efficient and cleaner combustion (minimum CO and dust content)
- **Vermiculite baffle**
- **Made of high quality** lamellar graphite cast iron
- **Double wall cast iron for extra strength**
- Removable cast iron grating
- High-strength **ceramic glass**

## INSTALLATION AND USE

- Back or top **flue connection** (150 mm)
- **Integrated handle** with a sleek design
- **Load facilitated by its high height**
- Adjustable primary and secondary air
- **"Clean glass" system**
- **Curved diagonal view** of 62 cm (24 inches)
- Removable **large capacity ashtray**

PRODUCT PERFORMANCE	
Nominal power	11.5 kW
Power range	7 to 14 kW
Efficiency	76%
Seasonal efficiency	66%
CO (13 % O <sub>2</sub> ) (mg/Nm <sup>3</sup> )	0.12 /1500
Nominal load	2.95 kg/h
Dust (mg/Nm <sup>3</sup> )	23
NOx (mg/Nm <sup>3</sup> )	98
VOC (OGC) (mg/Nm <sup>3</sup> )	85
Mean flue gas temperature	360 °C
Flue gas mass flow	9.7 g/s
Nozzle depression (nominal)	12 Pa
CO <sub>2</sub> emissions	9.14 %
Dual combustion	Yes
Airtight	No
ECODESING 2022	Yes

PRODUCT INFORMATION	
EAN Code:	376 007 <b>541 340 8</b>
Product code	FR9016190B
Main material	Cast iron
View of the fire (diagonal)	62 cm (26 inch)
Log size	33 cm (A) 50 cm (V)
Gross weight	192
Net weight	182
Dimensions LxHxD	48.4 x 112.5 x 47 cm
Size of pack LxHxD	60 x 126 x 58 cm

INSTALLATION AND SIZING	
Diameter of flue gas nozzle	150mm
Flue gas connection	Back or above part
Flue collar	Male
Back installation distance*	40cm
Lateral installation distance*	60cm

\*Distance between the heater and combustible materials

## PRODUCT PHOTOS



for a sleek design for a sleek design (MAONIE, MAONIE SUR PIED AND MAONIE BÜCHER).



Cast iron **hollow foot style**. Its rounded contours give MAONIE SUR PIED that special softness.

## DIMENSIONAL PLAN

