


**KAZETA L 67 VD 740/450,510**


Low-energy range 67

**Low-energy fireplace insert**


| Sizes |    |      | KAZETA L 67<br>VD 740/450 | KAZETA L 67<br>VD 740/510 |
|-------|----|------|---------------------------|---------------------------|
| 1     | A  | mm   | 740                       |                           |
| 2     | F  | mm   | 1060                      | 1120                      |
| 3     | C  | mm   | 480                       |                           |
| 4     | DN | Ø mm | 180                       |                           |
| 5     | B  | mm   | 450                       | 510                       |
| 6     | FF | mm   | 1350                      | 1470                      |
| 7     | V  | mm   | 850                       |                           |
| 8     | AA | mm   |                           |                           |
| 9     | H  | mm   | 315                       | 375                       |
| 10    | J  | mm   | 325 + /160/               |                           |
| 11    | K  | Ø mm | 4x125                     |                           |
| 12    | L  | Ø mm | 125                       |                           |
| 13    | M  | mm   | 20                        |                           |
| 14    | N  | mm   |                           |                           |

**Basic design:**

Thermodynamic Hearth  
 Segment chamotte lining  
 Glass Classic  
 Inox control grip-handle MP2  
 Enviromentally friendly varnish


**Optional accessories:**

Cover frame (KR)  
 Glass Reflex (SR)  
 Black printed glass(SM)  
 Black printed glass Reflex (SMR)  
 External ashtray (VOP)  
 Lower hearth (ZO)  
 Convectional casing (DP)  
 Rear feeding door (PD)  
 Vertical heat-storing panel (AZ)

| Technical parameters |  |                           |      |
|----------------------|--|---------------------------|------|
| 1                    | Nominal heat output                                      | kW                        | 6,5  |
| 2                    | Pressure required  | Pa                        | 12   |
| 3                    | Average efficiency                                       | %                         | 78   |
| 4                    | Average flue gas temperature                             | °C                        | 253  |
| 5                    | Wood consupcion  | kg/h                      | 2,1  |
| 6                    | Consumption of combustion air                            | m <sup>3</sup> /hod       | 19,5 |
| 7                    | Emission of CO to 13% O2                                 | %                         | 0,1  |
| 8                    | Flue gas mass flow                                       | g/s                       | 6,6  |
| 9                    | Weight   | kg                        | 250  |
| 10                   | Required min. cross section for circulating air - INPUT  | cm <sup>2</sup>           | 200  |
| 11                   | Required min. cross section for circulating air - OUTPUT | cm <sup>2</sup>           | 325  |
| 12                   | Three-component insulated chimney - active height 5 m    | Ø cm                      | 180  |
| 13                   | Character of building construction with fireplace insert | warm air convection       | Yes  |
|                      |  | heat storage without conv | No   |

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BlmSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk